



Sustainability data sheet

KORALAN® HOLZÖL (WOOD OIL)



1. Product description

Natural oil and water-based care oil

For initial coating and care of wooden elements, especially hardwoods. For wood in outdoor areas, for example garden furniture or grooved deck boards. Protects wooden surfaces from the effects of weather (sun, rain). Very good protection of the wood against greying.

2. Eco-labels and certifications



 Registered with DGNB registration code: 1SUCIW



Classified according to QNG



declared and validated product

Listed in baubook



 Fulfils the requirements of DIN EN 71-3 ("Safety of toys") in accordance with Directive 2009/48/EC

3. Ingredients

Product code / GISCODE	BSW30
VOC content (according to Directive 2004/42/EC)	<25 g/l
Dilutability with water (according to Directive 2004/42/EC)	Yes
Active substances for storage protection (incan preservative, product type 6)	Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3-one, 3-iodo-2-propinylbutylcarbamate
Active substances for coating protection (coating protection agent, product type 7)	Not part of the formula
Aromatic hydrocarbons	Not part of the formula
Plasticiser content according to VdL-RL 01	See safety data sheet (section 2 & 3)


ΕN

1/3











Sustainability data sheet

KORALAN® HOLZÖL (WOOD OIL)



Hazardous ingredients according to CLP regulation	Not part of the formula
CMR substances of categories 1A and 1B	Not part of the formula
PBT and vPvB substances	Not part of the formula
Ozone-depleting substances	Not part of the formula
Formaldehyde / Formaldehyde depot substances	Not part of the formula
Boron compounds toxic to reproduction ≤ 0.1%	met
Compliance with the limitation of emissions of the titanium dioxide industry	met

4. Information on building certification according to DGNB

Suitability for DGNB criterion ENV 1.2 (2023) "Risks for the local environment"

Product group No. 1	Coatings on non-mineral substrates: Metals, wood, plastics
Product type	This refers to decorative, fluid coating materials: var- nish/scumbles with primer coatings. Excluded are effect coatings (e.g. metallic paints)
DGNB quality level 1	met
DGNB quality level 2	met
DGNB quality level 3	met
DGNB quality level 4	Factory side: met On-site: not met

5. Information on building certification according to QNG

Annex document 3.1.3 Avoidance of harmful substances in building materials (as of 28 July 2023)


Building product group 6.1	On-site coatings on wood, metal and plastic in indoor and outdoor areas
Building products to be verified	All decorative coatings (1K and 2K systems) including primers and wood scumbles: Steel beams, sheet steel doors, interior doors, door frames, banisters, heating pipes, timber construction elements (beams, posts, transoms, purlins, etc.), timber panelling, façade cladding, etc except floor coverings

KORA°





2/3





Sustainability data sheet

KORALAN® HOLZÖL (WOOD OIL)



Substances analysed	VOC / hazardous substances / heavy metals (lead, cadmium, chromium VI)	
Regulations / reference standard	VOC according to 2004/42/EC, 1907/2006/EC, DE-UZ 12a	
QNG requirements for the avoidance of hazardous substances		
VOC ≤130 g/ml (water-based formula)	met	
No pigments and siccatives based on lead, cadmium and chromium VI compounds	met	

6. Quality and environmental management







7. Place of production

Kurt Obermeier GmbH Berghäuser Straße 70 57319 Bad Berleburg GERMANY

This data sheet has been compiled according to the latest state of the art and based on our experience. However, in view of the diverse requirements of building certifications, the buyer/user is not released from his/her obligation to check our assessment on his/her own responsibility for its suitability for the intended certification system and its respective requirements. This data sheet is only valid in its latest version and in conjunction with the current technical data sheet and the safety data sheet.

If necessary, please use our homepage to ensure that this version is up to date.







3/3